

PRODUCT CARD

GREENFOND Drain 250

GREENFOND Drain 250 drainage layer made of hardened polyethylene (HDPE) integrated with water permeable high quality filter geotextile

GREENFOND Drain 250 is designed for versatile use in the area where water insulation is needed, in both vertical and horizontal layout. In particular, it is used to drain water from pedestrian routes on driveways, in the area of extensive green roofs, terraces, foundation walls, bottom plates, bridgeheads, tunnels, etc. It can also be used to protect thermal insulation against mechanical damage and provide an additional supporting waterproofing barrier.

GREENFOND Drain 250 is used as a sealing layer for the construction of concrete structures for roadside drainage ditches and water reservoirs, provided that the layer covering the drainage mat is protected beforehand against lifting due to the buoyancy of the water below.



PRODUCT CARD

GREENFOND

Drain 250

TECHNICAL DATA OF THE PRODUCT:

Material	HDPE + PP
The height of the embossments	8 mm
Weight	740 g/m ²
Resistance to chemical compounds	Waterproof
Resistance to root overgrowth	no perforation at 200N/24h
Resistance to surface pressure	250 kN/m ²
Water drainage	MD 3,05 l / s x m -0,15 CMD 2,9 l / s x m - 0,15
Aging durability	meets the requirements
Roll dimension	2x15 m/30 m2
Pallet	6 rolls
Article numer	20.1202