

PRODUCT CARD

GREENFOND SK inspection chamber

GREENFOND SK inspection chamber used for revision of drainage point on green roofs and terraces

GREENFOND SK - the inspection chamber facilitates access to water drainage points from the green roof surface.

The construction of the inspection chamber is made of stainless steel A2 with a thickness of 1.5 mm, thus ensuring high resistance to all kinds of external factors.

The product complies with FLL guidelines for green roofs.

The inspection chamber is intended for flat green roofs as well as for roofs of the so-called ballast and gravel with the inclination angle of up to 15 °. The construction allows it to be used for gullies with a diameter of up to 250 mm.



GREENFOND SK Inspection chamber



GREENFOND SK N Extension for the inspection chamber

PRODUCT CARD

GREENFOND SK inspection chamber

BASIC TECHNICAL PARAMETERS AND CONTROL CHARACTERISTICS:

- Material: Acid resistant steel, 1.5 mm thick
- External dimensions of the inspection chamber: 40 cm x 40 cm
- Dimension of the side wall 30 cm x 30 cm
- Permissible load 250 kg
- Durability in natural soil: 20 years

INSTALLATION RECOMMENDATIONS

Place the box centrally over the roof gully.

When using drainage mats, the inspection chamber should be placed on the drain so that the drainage edges are invisible inside the chamber.

In the case of aggregate drainage, place the inspection chamber on the protective geotextile that is cut out so that the edges of the geotextile are invisible inside the chamber.

It is unacceptable to wrap up the inspection chamber with geotextile. The chamber cover should be placed approx. 2 cm below the top surface of the substrate.

PRODUCT CARD

GREENFOND

SK inspection chamber

AVAILABLE SIZE OF BOXES:		
Art. No.	PRODUCT NAME:	PRODUCT DESCRIPTION:
45.1201	GREENFOND SK 10 / 30 X 30	The inspection chamber with a lid / set / stainless steel, height 10 cm
45.1202	GREENFOND SK 15 / 30 X 30	The inspection chamber with a lid / set / stainless steel, height 15 cm
45.1203	GREENFOND SK 20 / 30 X 30	The inspection chamber with a lid / set / stainless steel, height 20 cm
45.1206	GREENFOND SK 30 / 30 X 30	The inspection chamber with a lid / set / stainless steel, height 30 cm
45.1207	GREENFOND SK 40 / 30 X 30	The inspection chamber with a lid / set / stainless steel, height 40 cm
45.1208	GREENFOND SK 50 / 30 X 30	The inspection chamber with a lid / set / stainless steel, height 50 cm
45.1209	GREENFOND SK 60 / 30 X 30	The inspection chamber with a lid / set / stainless steel, height 60 cm
45.1210	GREENFOND SK 80 / 30 X 30	The inspection chamber with a lid / set / stainless steel, height 80 cm
45.1211	GREENFOND SK 100 / 30 X 30	The inspection chamber with a lid / set / stainless steel, height 100 cm
45.1204	GREENFOND SK N5 / 30 X 30	Extension for the inspection chamber height 5 cm / base 30 x 30 cm
45.1205	GREENFOND SK N10 / 30 X 30	Extension for the inspection chamber height 10 cm / base 30 x 30 cm